

5000 -

200 000



200 000

IP 54

16 ,

| | |
|--|--|
| | 20E4 |
| | 250 PTI |
| | IP 40 IP 54 () |
| | -20 °C ... +85 °C -20 °C ... +55 °C |
| | UL 94 V-2 |
| | 850 °C |
| | PA, PA |
| | 64 |
| | ■ |
| | II |



5000 -

200 000

| | | | | | | | | | | | | | |
|-----------|---|--|----------------------|----------------------|----------------------|--|-----|---|----|----------|-----|--|-------|
| | / | | 4 (2) A 250 (.) 5E4 | 4 A 125 (.) 1/10 HP | 2 A 250 (.) 1/10 HP | | | | | | | | |
| | | | (SPNC) | | | | | | | | | | |
| 5000.0101 | | | * | * | * | | 2.8 | 3 | Ag | 2.0 ±0.4 | 4.0 | | * |
| 5000.0103 | | | * | * | * | | 2.8 | 3 | Ag | 2.0 ±0.4 | 4.0 | | * |
| 5000.0104 | | | * | * | * | | 2.8 | 3 | Ag | 2.0 ±0.4 | 4.0 | | * |
| 5000.0211 | | | * | * | * | | 2.8 | 3 | Ag | 2.0 ±0.4 | 4.0 | | * |
| 5000.0212 | | | * | * | * | | 2.8 | 3 | Ag | 2.0 ±0.4 | 4.0 | | |
| 5000.0501 | | | Z | Z | Z | | 2.8 | 3 | Ag | 2.0 ±0.4 | 4.0 | | IP 54 |

5000

X =

| | |
|-------------|------------|
| X | Ø |
| 1.4 ... 1.7 | 16.0 ±0.05 |

2.8 0.8 ()
5000.0211 5000.0212

2,8
IP54) 5000,0501